



## Spot 120 Dimmable 1-10V

■ 03.8052.14A1V - Black


Accent lighting LED module.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 539                 |
| Lamp category   | LED   | Mountings      | Track               |
| Power (W)       | 12W   | Environment    | Indoor dry location |
| CCT (K)         | 2700K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 11        |
| Beam angle C90-270 (°) | 11        |



|             |       |       |      |
|-------------|-------|-------|------|
| Beam Angle: | 11°   |       |      |
|             | h(m)  | E(lx) | D(m) |
| 1           | 11417 | 0.19  |      |
| 2           | 2854  | 0.37  |      |
| 3           | 1269  | 0.56  |      |
| 4           | 714   | 0.75  |      |
| 5           | 457   | 0.93  |      |

Luminous flux luminaire  
539 lm (EXTREME CUT OFF)



### Electrical

|             |                 |                  |     |
|-------------|-----------------|------------------|-----|
| Voltage (V) | 48              | Insulation class | III |
| Dimmable    | Yes             |                  |     |
| Driver      | Remote excluded |                  |     |
| Driver type | Dimmable 1-10V  |                  |     |
| Emergency   | Without         |                  |     |

### Physical

|              |            |             |     |
|--------------|------------|-------------|-----|
| Color        | Black      | Length (mm) | 185 |
| Orientation  | Adjustable |             |     |
| Weight (kg)  | 0.29       |             |     |
| Tilt (°)     | 90         |             |     |
| Rotation (°) | 360        |             |     |

### Note

Accessories included (honeycomb and screening crosspiece). Only compatible with 1-10V profile version.

