



Spot 120 Dimmable 1-10V

■ 03.8053.14A1V - Black


Accent lighting LED module.

Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 558 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 12W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |


Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 11 |
| Beam angle C90-270 (°) | 11 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 11° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 11834 | 0.19 | |
| 2 | 2958 | 0.37 | |
| 3 | 1315 | 0.56 | |
| 4 | 740 | 0.75 | |
| 5 | 473 | 0.93 | |

Luminous flux luminaire
558 lm (EXTREME CUT OFF)



Electrical

| | | | |
|--------------------|-----------------|-------------------------|-----|
| Voltage (V) | 48 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Dimmable 1-10V | | |
| Emergency | Without | | |

Physical

| | | | |
|---------------------|------------|--------------------|-----|
| Color | Black | Length (mm) | 185 |
| Orientation | Adjustable | | |
| Weight (kg) | 0.29 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

Accessories included (honeycomb and screening crosspiece). Only compatible with 1-10V profile version.

