



Spot 150 Casambi integrated

New

03.8072.05.CB - Polished Aluminium


Accent lighting LED module.

Main specifications

Number of heads	1	Net lumen (lm)	1910
Lamp category	LED	Mountings	Track
Power (W)	22.5W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16



Beam Angle: 16°

h(m)	E(lx)	D(m)
1	17679	0.28
2	4420	0.56
3	1964	0.84
4	1105	1.12
5	707	1.40

Luminous flux luminaire
1910 lm



Electrical


Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
	Casambi		
Emergency	Without		

Physical

Color	Polished Aluminium	Length (mm)	245
Orientation	Adjustable		
Weight (kg)	0.42		
Tilt (°)	90		
Rotation (°)	360		

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.



Spot 150 Casambi integrated



Screening crosspiece
08.8429.00



Snoot shielding cone
08.0526.BW



Snoot shielding cone
08.0526.40




Honeycomb
08.8428.00



Snoot shielding cone
08.0526.00



Flood lens
08.8432.00



Elliptical lens
08.8431.00