



Spot 150 Casambi integrated

New

■ 03.8073.14.CB - Black


Accent lighting LED module.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	2019
Power (W)	22.5W	Mountings	Track
System power (W)	22.5	Environment	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16
UGRL	4
Efficiency (lm/W)	89.73



Beam Angle: 16°

h(m) E(lx) D(m)

1 18695 0.28

2 4674 0.56

3 2077 0.84

4 1168 1.12

5 748 1.40

Luminous flux luminaire
2019 lm

Electrical



Voltage (V)	48	Emergency	Without
Current (mA)	600	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		

Physical

Color	Black	Spot diameter (mm)	57
Orientation	Adjustable	Length (mm)	178
Weight (kg)	0.42	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.



Spot 150 Casambi integrated



Snoot shielding cone
08.0526.00



Flood lens
08.8432.00



Snoot shielding cone
08.0526.40




Honeycomb
08.8428.00



Snoot shielding cone
08.0526.BW



Screening crosspiece
08.8429.00



Elliptical lens
08.8431.00