



## Spot 150 Casambi integrated

New

03.8073.40.CB - White


Accent lighting LED module.

### Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 2019                |
| Power (W)        | 22.5W | Mountings      | Track               |
| System power (W) | 22.5  | Environment    | Indoor dry location |
| CCT (K)          | 3000K |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 16        |
| Beam angle C90-270 (°) | 16        |
| UGRL                   | 4         |
| Efficiency (lm/W)      | 89.73     |



Beam Angle: 16°

h(m) E(lx) D(m)

1 18695 0.28

2 4674 0.56

3 2077 0.84

4 1168 1.12

5 748 1.40

Luminous flux luminaire  
2019 lm

### Electrical



|              |                     |                  |         |
|--------------|---------------------|------------------|---------|
| Voltage (V)  | 48                  | Emergency        | Without |
| Current (mA) | 600                 | Insulation class | III     |
| Dimmable     | Yes                 |                  |         |
| Driver       | Remote<br>excluded  |                  |         |
| Driver type  | Dimmable<br>Casambi |                  |         |

### Physical

|              |            |                    |        |
|--------------|------------|--------------------|--------|
| Color        | White      | Spot diameter (mm) | 57     |
| Orientation  | Adjustable | Length (mm)        | 178    |
| Weight (kg)  | 0.42       | Lifespan (L70 B10) | L80B50 |
| Tilt (°)     | 90         |                    |        |
| Rotation (°) | 360        |                    |        |

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.



Spot 150 Casambi integrated



---

Snoot shielding cone  
08.0526.00



---

Flood lens  
08.8432.00



---

Screening crosspiece  
08.8429.00



---

Snoot shielding cone  
08.0526.40




---

Honeycomb  
08.8428.00



---

Snoot shielding cone  
08.0526.BW



---

Elliptical lens  
08.8431.00