

Spot 150 Dali Version

03.8073.05.DA - Polished Aluminium

Accent lighting LED module.




Main specifications

Number of heads	1	Net lumen (lm)	2019
Lamp category	LED	Mountings	Track
Power (W)	22.5W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16



Beam Angle: 16°

	h(m)	E(lx)	D(m)
1	18695	0.28	
2	4674	0.56	
3	2077	0.84	
4	1168	1.12	
5	748	1.40	

Luminous flux luminaire
2019 lm



Electrical



Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable DALI 1		
Emergency	Without		

Physical

Color	Polished Aluminium	Length (mm)	245
Orientation	Adjustable		
Weight (kg)	0.42		
Tilt (°)	90		
Rotation (°)	360		

Note


Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time. Only compatible with DALI profile version.



Spot 150 Dali Version



Flood lens
08.8432.00



Elliptical lens
08.8431.00



Snoot shielding cone
08.0526.40



Snoot shielding cone
08.0526.BW



Screening crosspiece
08.8429.00



Honeycomb
08.8428.00



Snoot shielding cone
08.0526.00