



## Spot 150 Dali Version

■ 03.8073.14.DA - Black


Accent lighting LED module.

### Main specifications

<b>Number of heads</b>	1	<b>CRI</b>	90
<b>Lamp category</b>	LED	<b>Net lumen (lm)</b>	2019
<b>Power (W)</b>	22.5W	<b>Mountings</b>	Track
<b>System power (W)</b>	22.5	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	16
<b>Beam angle C90-270 (°)</b>	16
<b>UGRL</b>	4
<b>Efficiency (lm/W)</b>	89.73



Beam Angle: 16°

	h(m)	E(lx)	D(m)
1	18695	0.28	
2	4674	0.56	
3	2077	0.84	
4	1168	1.12	
5	748	1.40	

Luminous flux luminaire  
2019 lm



### Electrical



<b>Voltage (V)</b>	48	<b>Emergency</b>	Without
<b>Current (mA)</b>	600	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmable DALI		
	1		

### Physical

<b>Color</b>	Black	<b>Spot diameter (mm)</b>	57
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	178
<b>Weight (kg)</b>	0.42	<b>Lifespan (L70 B10)</b>	L80B50
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time. Only compatible with DALI profile version.




## Spot 150 Dali Version



---

Screening crosspiece  
08.8429.00



---

Elliptical lens  
08.8431.00



---

Snoot shielding cone  
08.0526.00



---

Flood lens  
08.8432.00



---

Snoot shielding cone  
08.0526.40



---

Honeycomb  
08.8428.00



---

Snoot shielding cone  
08.0526.BW