

## Spot 150 Dali Version

03.8074.05.DA - Polished Aluminium

Accent lighting LED module.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1910
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	22.5W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	28
<b>Beam angle C90-270 (°)</b>	28



<b>Beam Angle:</b>	28°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	8828	0.50	
2	2207	1.00	
3	981	1.50	
4	552	2.00	
5	353	2.50	

Luminous flux luminaire  
1910 lm



### Electrical



<b>Voltage (V)</b>	48.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmable DALI 1		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Polished Aluminium	<b>Length (mm)</b>	245
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	0.42		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time. Only compatible with DALI profile version.



## Spot 150 Dali Version




---

Snoot shielding cone  
08.0526.BW



---

Snoot shielding cone  
08.0526.00



---

Elliptical lens  
08.8431.00



---

Screening crosspiece  
08.8429.00



---

Snoot shielding cone  
08.0526.40



---

Flood lens  
08.8432.00



---

Honeycomb  
08.8428.00