



Spot 150 Dali Version

■ 03.8076.14.DA - Black


Accent lighting LED module.

Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 1853 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 22.5W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 40 |
| Beam angle C90-270 (°) | 40 |



| | | | |
|--------------------|-------------|--------------|-------------|
| Beam Angle: | 40° | | |
| | h(m) | E(lx) | D(m) |
| | 1 | 4693 | 0.73 |
| | 2 | 1173 | 1.46 |
| | 3 | 521 | 2.18 |
| | 4 | 293 | 2.91 |
| | 5 | 188 | 3.64 |

Luminous flux luminaire
1853 lm



Electrical



| | | | |
|--------------------|-----------------|-------------------------|-----|
| Voltage (V) | 48.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Dimmable DALI 1 | | |
| Emergency | Without | | |

Physical

| | | | |
|---------------------|------------|--------------------|-----|
| Color | Black | Length (mm) | 245 |
| Orientation | Adjustable | | |
| Weight (kg) | 0.42 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time. Only compatible with DALI profile version.



Spot 150 Dali Version



Honeycomb
08.8428.00



Snoot shielding cone
08.0526.BW



Snoot shielding cone
08.0526.00



Elliptical lens
08.8431.00



Screening crosspiece
08.8429.00



Snoot shielding cone
08.0526.40



Flood lens
08.8432.00