



## Spot 150 On Board Dimmer

03.8077.05 - Polished Aluminium


Accent lighting LED module.

### Main specifications

Number of heads	1	Net lumen (lm)	1983
Lamp category	LED	Mountings	Track
Power (W)	22.5W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	40
Beam angle C90-270 (°)	40



Beam Angle:	40°		
	h(m)	E(lx)	D(m)
1	5023	0.73	
2	1256	1.46	
3	558	2.18	
4	314	2.91	
5	201	3.64	

Luminous flux luminaire  
1983 lm



### Electrical



Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmer on board		
Emergency	Without		

### Physical

Color	Polished Aluminium	Length (mm)	245
Orientation	Adjustable		
Weight (kg)	0.42		
Tilt (°)	90		
Rotation (°)	360		

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



## Spot 150 On Board Dimmer



---

Screening crosspiece  
08.8429.00



---

Snoot shielding cone  
08.0526.40



---

Flood lens  
08.8432.00



---

Honeycomb  
08.8428.00



---

Snoot shielding cone  
08.0526.BW



---

Snoot shielding cone  
08.0526.00



---

Elliptical lens  
08.8431.00