



Spot 90 Casambi integrated

New

03.8044.05ACB - Polished Aluminium


Accent lighting LED module.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	392
Power (W)	8.5W	Mountings	Track
System power (W)	8.7	Environment	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22
UGRL	4
Efficiency (lm/W)	45.06



Beam Angle: 22°

h(m) E(lx) D(m)

1 2319 0.38

2 580 0.77

3 258 1.15

4 145 1.54

5 93 1.92

Luminous flux luminaire
392 lm (EXTREME CUT OFF)

Electrical

Voltage (V)	48	Emergency	Without
Current (mA)	600	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		

Physical

Color	Polished Aluminium	Spot diameter (mm)	35
Orientation	Adjustable	Length (mm)	178
Weight (kg)	0.17	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

Accessories not suitable for chrome finishes. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

