



## Spot 90 Dali Version

03.8044.40ADA - White


Accent lighting LED module.

### Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 392                 |
| Power (W)        | 8.5W  | Mountings      | Track               |
| System power (W) | 8.7   | Environment    | Indoor dry location |
| CCT (K)          | 2700K |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 22        |
| Beam angle C90-270 (°) | 22        |
| UGRL                   | 4         |
| Efficiency (lm/W)      | 45.06     |



Beam Angle: 22°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2319  | 0.38 |
| 2    | 580   | 0.77 |
| 3    | 258   | 1.15 |
| 4    | 145   | 1.54 |
| 5    | 93    | 1.92 |

Luminous flux luminaire  
392 lm (EXTREME CUT OFF)

### Electrical

|              |                 |                  |         |
|--------------|-----------------|------------------|---------|
| Voltage (V)  | 48              | Emergency        | Without |
| Current (mA) | 600             | Insulation class | III     |
| Dimmable     | Yes             |                  |         |
| Driver       | Remote excluded |                  |         |
| Driver type  | Dimmable DALI 1 |                  |         |

### Physical

|              |            |                    |        |
|--------------|------------|--------------------|--------|
| Color        | White      | Spot diameter (mm) | 35     |
| Orientation  | Adjustable | Length (mm)        | 178    |
| Weight (kg)  | 0.17       | Lifespan (L70 B10) | L80B50 |
| Tilt (°)     | 90         |                    |        |
| Rotation (°) | 360        |                    |        |

### Note

Accessories included (honeycomb and screening crosspiece). Only compatible with DALI profile version.

