



# Spot 90 On Board Dimmer 03.8043.05A - Polished Aluminium

Accent lighting LED module.


## Main specifications

Number of heads LED Lamp category Power (W) 8.5W System power (W) CCT (K) 8.6 3000K CRI 90 443 Net lumen (lm) Mountings Track

Environment Indoor dry location

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	14
Beam angle C90-270 (°)	14
UGRL :	3
Efficiency (lm/W)	51.51



h(m) = E(Ix)D(m) 5805 0.25 2 1451 0.49 3 645 0.74 363 0.98 232 1.23

Beam Angle:

14°

Luminous flux luminaire (EXTREME CUT OFF)

**Emergency** Insulation class Without

### Electrical

voitage (v)	40
Current (mA)	600
Dimmable	Yes
Driver	Remote
	excluded
Driver type	Dimmer on
	1 1

10

## Voltage (V)


Current (mA)	600
Dimmable	Yes
Driver	Remote
	excluded
Driver type	Dimmer on
	board

# Physical

yo.ou.		
Color	Polished	Spot diameter (mm) 35
	Aluminium	Length (mm) 178
Orientation	Adjustable	Lifespan (L70 B10) L80B50
Weight (kg)	0.17	
Tilt (°)	90	
Rotation (°)	360	

## Note

Accessories not suitable for chrome finishes.



EHI CE RETILAP







