


Spot Module Casambi integrated

New

03.6302.14BCB - Black

Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.




Main specifications

Number of heads	1	Net lumen (lm)	418
Lamp category	LED	Mountings	Track
Power (W)	8W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	14
Beam angle C90-270 (°)	14



Beam Angle:	14°
h(m)	E(lx) D(m)
1	5973 0.24
2	1493 0.49
3	664 0.73
4	373 0.98
5	239 1.22

Luminous flux luminaire
418 lm

Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		
Emergency	Without		

Physical

Color	Black	Spot diameter (mm)	34
Orientation	Adjustable	Length (mm)	34
Weight (kg)	0.19		
Tilt (°)	90		
Rotation (°)	360		

Note

Maximum 21 spots for a single driver. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.

Spot Module Casambi integrated



Elliptical Lens
08.8759.00



Frosted Flood lens
08.8761.00



Screening external ring for Running
Magnet spot module
08.8427.14



Frosted Medium lens
08.8760.00