


Spot Module Casambi integrated

New

■ 03.6303.14BCB - Black

Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.




Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	403
Power (W)	8W	Mountings	Track
System power (W)	8.4	Environment	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	14
Beam angle C90-270 (°)	14
UGRL	14
Efficiency (lm/W)	47.98



Beam Angle: 14°

h(m) E(lx) D(m)

1 5763 0.24

2 1441 0.49

3 640 0.73

4 360 0.98

5 231 1.22

Luminous flux luminaire
403 lm

Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		
Emergency	Without		

Physical


Color	Black	Spot diameter (mm)	34
Orientation	Adjustable	Length (mm)	34
Weight (kg)	0.19	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

Maximum 21 spots for a single driver. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.



Spot Module Casambi integrated



Screening external ring for Running
Magnet spot module
08.8427.14



Frosted Flood lens
08.8761.00



Elliptical Lens
08.8759.00



Frosted Medium lens
08.8760.00