

Spot Module LED Array

■ 09.0212.14A - Black


Spotlight to be installed on Light Cut Mini system. Remote continuous current supply source not included.

Main specifications

Lamp category	LED	Mountings	Track
Power (W)	14.4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		
Net lumen (lm)	1174		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	32
Beam angle C90-270 (°)	32



Beam Angle: 32°

h(m)	E(lx)	D(m)
1	3137	0.57
2	784	1.13
3	349	1.70
4	196	2.26
5	125	2.83

Luminous flux luminaire
1174 lm



Electrical

Voltage (V)	32.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1		
	Without		

Emergency

Physical

Color	Black	Spot diameter (mm)	60.00
Orientation	Adjustable		
Weight (kg)	0.30		
Tilt (°)	180		
Rotation (°)	360		



Spot Module LED Array



HOT LIGHT
08.8501.69



COLD LIGHT
08.8501.CL



Continuous current power supply of
18W, 220/240V – 50/60Hz with 450 mA
supply voltage Mains dimming, trailing
edge
60.9268



BLUE FILTER
08.8501.64.OD



Continuous current power supply,
dimmable Casambi 220/240V-50/60Hz,
300mA-16W / 350mA-18,5W / 400mA-
21,5W / 450mA-24W / 500mA-27W /
600mA-32W / 650mA-35W / 700mA-36W
/750/800/900/1000/1050mA – 38W
60.9207



Continuous current power supply of
10-20W, 110/240V – 50/60Hz with power
current selected through adjustable
250 mA – 10W / 350 mA – 15W / 400 mA
– 17W / 450 mA – 19W / 500/550/600/700
mA – 20W, Dali 1 switch.
60.8847



Continuous current power supply of
13-20W, 110/240V – 50/60Hz with power
current selected through adjustable
300 mA – 15W / 350 mA – 18W /
400/450/500/550/600/
650/700/750/800/850/900 mA – 15W.
switch. 0/1-10V or push dimming
60.9188

SKY BLUE FILTER
08.8501.65.OD

RED FILTER
08.8501.67.OD



NEODIMIUM
08.8501.ND

Honeycomb
08.8502.14

Non dimmable continuous current
power supply of 220/240V – 50/60Hz
with power current selected through
adjustable with switch 200 mA – 8,5W /
300 mA – 13W / 350 mA – 15W / 400 mA
– 17,5W / 450 mA – 19,5W / 500 mA –
22W
60.9160



DAYLIGHT
08.8501.DL

AMBER FILTER
08.8501.66.OD