

Spot Module LED Array

09.0217.30A - White


Spotlight to be installed on Light Cut Mini system. Remote continuous current supply source not included.

Main specifications

Lamp category	LED	Mountings	Track
Power (W)	14.4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	1006		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	28
Beam angle C90-270 (°)	28



Beam Angle: 28°

h(m)	E(lx)	D(m)
1	3226	0.49
2	806	0.99
3	358	1.48
4	202	1.98
5	129	2.47



Luminous flux luminaire
1006 lm

Electrical

Voltage (V)	32.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	White	Spot diameter (mm)	60.00
Orientation	Adjustable		
Weight (kg)	0.30		
Tilt (°)	180		
Rotation (°)	360		



Spot Module LED Array



Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/ 650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming
60.9188

BLUE FILTER
08.8501.64.OD

Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200 mA – 8,5W / 300 mA – 13W / 350 mA – 15W / 400 mA – 17,5W / 450 mA – 19,5W / 500 mA – 22W
60.9160



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W
60.9207

Honeycomb
08.8502.14

AMBER FILTER
08.8501.66.OD



NEODIMIUM
08.8501.ND



COLD LIGHT
08.8501.CL



Continuous current power supply of
18W, 220/240V – 50/60Hz with 450 mA
supply voltage Mains dimming, trailing
edge
60.9268



HOT LIGHT
08.8501.69



Continuous current power supply of
10-20W, 110/240V – 50/60Hz with power
current selected through adjustable
250 mA – 10W / 350 mA – 15W / 400 mA
– 17W / 450 mA – 19W / 500/550/600/700
mA – 20W, Dali 1 switch.
60.8847



RED FILTER
08.8501.67.OD



DAYLIGHT
08.8501.DL



SKY BLUE FILTER
08.8501.65.OD