



Spot Module Pro LED Array

■ 09.0361.14 - Black

Spotlight to be installed on Light Cut Mini system. Remote continuous current supply source not included.




Main specifications

Lamp category	LED	Mountings	Track
Power (W)	18W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	1207		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	20
Beam angle C90-270 (°)	20



Beam Angle: 20°

h(m)	E(lx)	D(m)
1	6553	0.35
2	1638	0.71
3	728	1.06
4	410	1.41
5	262	1.77

Luminous flux luminaire
1207 lm

Electrical

Voltage (V)	34.50	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	Black	Spot diameter (mm)	60.00
Orientation	Adjustable		
Weight (kg)	1.2		
Tilt (°)	180		
Rotation (°)	360		

Note

High performance part numbers include high performance reflector.

Spot Module Pro LED Array



Flood lens
08.3310.19



Non dimmable continuous current
power supply of 220/240V – 50/60Hz
with power current selected through
adjustable with switch 200 mA – 8,5W /
300 mA – 13W / 350 mA – 15W / 400 mA
– 17,5W / 450 mA – 19,5W / 500 mA –
22W
60.9160



Continuous current power supply of
13-20W, 110/240V – 50/60Hz with power
current selected through adjustable
300 mA – 15W / 350 mA – 18W /
400/450/500/550/600/
650/700/750/800/850/900 mA – 15W.
switch. 0/1-10V or push dimming
60.9188



Continuous current power supply of
10-20W, 110/240V – 50/60Hz with power
current selected through adjustable
250 mA – 10W / 350 mA – 15W / 400 mA
– 17W / 450 mA – 19W / 500/550/600/700
mA – 20W, Dali 1 switch.
60.8847



Honeycomb
08.3309.14



Elliptical lens
08.8627.68



Continuous current power supply of
12-20W, 110/240V – 50/60Hz with power
current selected through adjustable
350mA – 17W / 400mA – 19W / 450 / 550
/ 600 / 700mA – 20W regulable Dali 1 y
Dali 2
60.9222

Continuous current power supply,
Mains dimming, leading & trailing edge
220/240V – 50/60Hz, 300mA-14W /
350mA-17W / 400mA-19W /
450/500/600/650/700/750/800/900mA –
20W
60.9467

Continuous current power supply,
dimmable Casambi 220/240V-50/60Hz,
300mA-16W / 350mA-18,5W / 400mA-
21,5W / 450mA-24W / 500mA-27W /
600mA-32W / 650mA-35W / 700mA-36W
/750/800/900/1000/1050mA – 38W
60.9207