


Spot Module Pro LED Array

09.0361.30 - White

Spotlight to be installed on Light Cut Mini system. Remote continuous current supply source not included.




Main specifications

Lamp category	LED	Mountings	Track
Power (W)	18W	Environment	Indoor
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	1207		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	20
Beam angle C90-270 (°)	20



Beam Angle: 20°	h(m)	E(lx)	D(m)
1	6553	0.35	
2	1638	0.71	
3	728	1.06	
4	410	1.41	
5	262	1.77	

Luminous flux luminaire
1207 lm

Electrical


Voltage (V)	34.50	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable push, Electronic dimmable 1-10V, Electronic dimmable DALI		
Emergency	Without		

Physical

Color	White	Spot diameter (mm)	60.00
Orientation	Adjustable		
Weight (kg)	1.2		
Tilt (°)	180		
Rotation (°)	360		

Note

High performance part numbers include high performance reflector.



Spot Module Pro LED Array



Honeycomb
08.3309.14



Elliptical lens
08.8627.68



Flood lens
08.3310.19



Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200 mA – 8,5W / 300 mA – 13W / 350 mA – 15W / 400 mA – 17,5W / 450 mA – 19,5W / 500 mA – 22W
60.9160



Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming
60.9188



Continuous current power supply of 10-20W, 110/240V – 50/60Hz with power current selected through adjustable 250 mA – 10W / 350 mA – 15W / 400 mA – 17W / 450 mA – 19W / 500/550/600/700 mA – 20W, Dali 1 switch.
60.8847



Continuous current power supply of



Continuous current power supply,



Continuous current power supply,

350mA – 17W / 400mA – 19W / 450 / 550
/ 600 / 700mA – 20W regulable Dali 1 y
Dali 2
60.9222

350mA-17W / 400mA-19W /
450/500/600/650/700/750/800/900mA –
20W
60.9467

400mA-21,5W / 450mA-24W / 500mA-
27W / 600mA-32W / 650mA-35W /
700mA-36W / 750/800/900/1000/1050mA
– 38W
60.9207