



Spot Module Pro LED Array

■ 09.0367.14 - Black

Spotlight to be installed on Light Cut Mini system. Remote continuous current supply source not included.




Main specifications

Lamp category	LED	Mountings	Track
Power (W)	18W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	1699		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	37
Beam angle C90-270 (°)	37



Beam Angle: 37°

h(m)	E(lx)	D(m)
1	4687	0.67
2	1172	1.34
3	521	2.00
4	293	2.67
5	187	3.34

Luminous flux luminaire
1699 lm

Electrical

Voltage (V)	34.50	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	Black	Spot diameter (mm)	60.00
Orientation	Adjustable		
Weight (kg)	1.2		
Tilt (°)	180		
Rotation (°)	360		

Note

High performance part numbers include high performance reflector.

Spot Module Pro LED Array



Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/ 650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming 60.9188

Continuous current power supply of 10-20W, 110/240V – 50/60Hz with power current selected through adjustable 250 mA – 10W / 350 mA – 15W /400 mA – 17W /450 mA – 19W /500/550/600/700 mA – 20W, Dali 1 switch. 60.8847

Continuous current power supply of 12-20W, 110/240V – 50/60Hz with power current selected through adjustable 350mA – 17W / 400mA – 19W / 450 / 550 / 600 / 700mA – 20W regulable Dali 1 y Dali 2 60.9222



Honeycomb
08.3309.14

Elliptical lens
08.8627.68

Flood lens
08.3310.19



Non dimmable continuous current

Continuous current power supply,

Continuous current power supply,

adjustable with switch 200 mA – 8,5W /	350mA-17W / 400mA-19W /	21,5W / 450mA-24W / 500mA-27W /
300 mA – 13W / 350 mA – 15W / 400 mA	450/500/600/650/700/750/800/900mA –	600mA-32W / 650mA-35W / 700mA-36W
– 17,5W / 450 mA – 19,5W / 500 mA –	20W	/750/800/900/1000/1050mA – 38W
22W	60.9467	60.9207
60.9160		