



String Light Sphere Casambi integrated

New

03.6296.14.CB - Black


General lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	836
Power (W)	16W	Mountings	Track
System power (W)	16.5	Environment	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Diffused light
Efficiency (lm/W)	50.67



Beam Angle DIR: 178°

h(m)	E(lx)	D(m)
1	135	112.78
2	34	225.57
3	15	338.35
4	8	451.13
5	5	563.91

Luminous flux luminaire
836 lm

Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
Emergency	Casambi		
	Without		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	1.27
Length (mm)	190
Lifespan (L70 B10)	L80B50

Note

Maximum 9 spots for a single driver. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.

