



Super Flat Surface 120x30 Dali Version

■ 09.6040.02BDA - Grey

Surface mounted general lighting LED luminaire. Power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	4441
Lamp category	LED	Mountings	Ceiling surface
Power (W)	56W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	105
Beam angle C90-270 (°)	96



Beam Angle: 105°

$h(m)$	$E(I_x)$	$D(m)$
1	1529	2.62
2	382	5.25
3	170	7.87
4	96	10.49
5	61	13.12

Luminous flux luminaire
4441 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	35.00	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		

Physical

Color	Grey
Orientation	Fixed
Weight (kg)	5.80

Note

Total consumption of the system: 56W. Light source: max. 6964 lm. Luminous efficiency of luminaire: max. 138 lm/W.