

Super Flat Surface 120x30 Dali Version

■ 09.6041.14BDA - Black


Surface mounted general lighting LED luminaire. Power supply included.

Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 4622 |
| Lamp category | LED | Mountings | Ceiling surface |
| Power (W) | 56W | Environment | Indoor dry location |
| CCT (K) | 4000K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|------------|
| Lighting type | Direct |
| LED type | Top LED |
| Light distribution | Symmetric |
| Optical type | Wide flood |
| Beam angle (°) | 105 |
| Beam angle C90-270 (°) | 96 |



Beam Angle: 105°

| h(m) | E(lx) | D(m) |
|------|-------|-------|
| 1 | 1592 | 2.62 |
| 2 | 398 | 5.25 |
| 3 | 177 | 7.87 |
| 4 | 99 | 10.49 |
| 5 | 64 | 13.12 |

Luminous flux luminaire
4622 lm (EXTREME CUT OFF)

Electrical

| | | | |
|----------------|---------------|------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 35.00 | Insulation class | I |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical

| | |
|-------------|-------|
| Color | Black |
| Orientation | Fixed |
| Weight (kg) | 5.80 |

Note

Total consumption of the system: 56W. Light source: max. 7660 lm. Luminous efficiency of luminaire: max. 151 lm/W.

