


## Super Flat Surface 120x30 No Dimmable

09.6040.30B - White

Surface mounted general lighting LED luminaire. Power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	4441
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	56W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	105
<b>Beam angle C90-270 (°)</b>	96



Beam Angle: 105°		
h(m)	E(lx)	D(m)
1	1529	2.62
2	382	5.25
3	170	7.87
4	96	10.49
5	61	13.12


Luminous flux luminaire  
4441 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	35.00	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Electronic		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	5.80



### Note

Total consumption of the system: 56W. Light source: max. 6964 lm. Luminous efficiency of luminaire: max. 138 lm/W.