



Super Flat Surface 90x90 No Dimmable

■ 09.6020.02B - Grey

Surface mounted general lighting LED luminaire. Power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	4802
Lamp category	LED	Mountings	Ceiling surface
Power (W)	55W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	104
Beam angle C90-270 (°)	107



Beam Angle: 104°		
<u>h(m)</u>	<u>E(lx)</u>	<u>D(m)</u>
1	1804	2.58
2	451	5.15
3	200	7.73
4	113	10.31
5	72	12.88

Luminous flux luminaire
4802 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	35.00	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

Physical

Color	Grey
Orientation	Fixed
Weight (kg)	9.90

Note

Total consumption of the system: 55W. Light source: max. 6964 lm. Luminous efficiency of luminaire: max. 138 lm/W.