

## Super Flat Suspension 120x20 Down No Dimmable

■ 09.5030.02B - Grey


General lighting LED luminaire to be suspended from ceiling. Power supply included.

### Main specifications

|                 |       |                |            |
|-----------------|-------|----------------|------------|
| Number of heads | 1     | Net lumen (lm) | 3765       |
| Lamp category   | LED   | Mountings      | Suspension |
| Power (W)       | 56W   | Environment    | Indoor     |
| CCT (K)         | 3000K |                |            |
| CRI             | 90    |                |            |

### Optical

|                        |            |
|------------------------|------------|
| Lighting type          | Direct     |
| LED type               | Top LED    |
| Light distribution     | Symmetric  |
| Optical type           | Wide flood |
| Beam angle (°)         | 104        |
| Beam angle C90-270 (°) | 94         |



Beam Angle: 104°

| h(m) | E(lx) | D(m)  |
|------|-------|-------|
| 1    | 1289  | 2.57  |
| 2    | 322   | 5.14  |
| 3    | 143   | 7.71  |
| 4    | 81    | 10.28 |
| 5    | 52    | 12.86 |

Luminous flux luminaire  
3765 lm (EXTREME CUT OFF)

### Electrical

|                |            |                  |         |
|----------------|------------|------------------|---------|
| Frequency (Hz) | 50/60      | Emergency        | Without |
| Voltage (V)    | 35.00      | Insulation class | I       |
| Dimmable       | No         |                  |         |
| Driver         | Integrated |                  |         |
| Driver type    | Electronic |                  |         |

### Physical

|             |       |
|-------------|-------|
| Color       | Grey  |
| Orientation | Fixed |
| Weight (kg) | 3.28  |

### Note

Total consumption of the system: 56W. Light source: max. 6964 lm. Luminous efficiency of luminaire: max. 138 lm/W.