

Super Flat Suspension 120x20 Up&Down Dali Version

■ 09.5036.02BDA - Grey


General lighting LED luminaire, direct and indirect beam, to be suspended from ceiling. Power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	3526
Lamp category	LED	Mountings	Suspension
Power (W)	56W	Environment	Indoor
CCT (K)	4000K		
CRI	90		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	108
Beam angle C90-270 (°)	88



Beam Angle DIR: 108°

h(m)	E(lx)	D(m)
1	553	2.74
2	138	5.47
3	61	8.21
4	35	10.94
5	22	13.68

Luminous flux luminaire
3526 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Insulation class	I
Voltage (V)	35.00		
Dimmable	Yes		
Driver	Integrated		
Emergency	Without		

Physical

Color	Grey
Orientation	Fixed
Weight (kg)	3.28

Note

Total consumption of the system: 56W. Light source: Up: max. 3830 lm. Down: max. 3830 lm. Luminous efficiency of luminaire: max. 151 lm/W.