

Super Flat Suspension 120x30 Down Dali Version

09.5040.14BDA - Black

General lighting LED luminaire to be suspended from ceiling. Power supply included.

Main specifications

Number of heads	1	**Net lumen (lm)**	4441
Lamp category	LED	**Mountings**	Suspension
Power (W)	56W	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	105
Beam angle C90-270 (°)	96



Luminous flux luminaire
4441 lm (EXTREME CUT OFF)

Beam Angle: 105°

h(m)	E(lx)	D(m)
1	1529	2.62
2	382	5.25
3	170	7.87
4	96	10.49
5	61	13.12

Electrical

Frequency (Hz)	50/60	**Emergency**	Without
Voltage (V)	35.00	**Insulation class**	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI 1		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	4.20

Note

Total consumption of the system: 56W. Light source: max. 6964 lm. Luminous efficiency of luminaire: max. 138 lm/W.