



## Super Flat Suspension 120x30 Down Dali Version

■ 09.5041.02BDA - Grey


General lighting LED luminaire to be suspended from ceiling. Power supply included.

### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Suspension
<b>Power (W)</b>	56W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	4000K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	4622		

### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	105
<b>Beam angle C90-270 (°)</b>	96



Beam Angle: 105°

	h(m)	E(lx)	D(m)
1	1592	2.62	
2	398	5.25	
3	177	7.87	
4	99	10.49	
5	64	13.12	

Luminous flux luminaire  
4622 lm (EXTREME CUT OFF)




### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Voltage (V)</b>	35.00		
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Grey
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	4.20



### Note

Total consumption of the system: 56W. Light source: max. 7660 lm. Luminous efficiency of luminaire: max. 151 lm/W.