



## Super Flat Suspension 120x30 Up&Down No Dimmable

09.5045.30B - White


General lighting LED luminaire, direct and indirect beam, to be suspended from ceiling. Power supply included.

### Main specifications

|                        |       |                       |            |
|------------------------|-------|-----------------------|------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 4225       |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Suspension |
| <b>Power (W)</b>       | 56W   | <b>Environment</b>    | Indoor     |
| <b>CCT (K)</b>         | 3000K |                       |            |
| <b>CRI</b>             | 90    |                       |            |

### Optical


|                               |                  |
|-------------------------------|------------------|
| <b>Lighting type</b>          | Indirect, Direct |
| <b>LED type</b>               | Top LED          |
| <b>Light distribution</b>     | Symmetric        |
| <b>Optical type</b>           | Wide flood       |
| <b>Beam angle (°)</b>         | 109              |
| <b>Beam angle C90-270 (°)</b> | 91               |



Beam Angle DIR: 109°

| h(m) | E(lx) | D(m)  |
|------|-------|-------|
| 1    | 632   | 2.82  |
| 2    | 158   | 5.64  |
| 3    | 70    | 8.46  |
| 4    | 40    | 11.27 |
| 5    | 25    | 14.09 |

Luminous flux luminaire  
4225 lm (EXTREME CUT OFF)




### Electrical

|                       |            |                         |         |
|-----------------------|------------|-------------------------|---------|
| <b>Frequency (Hz)</b> | 50/60      | <b>Emergency</b>        | Without |
| <b>Voltage (V)</b>    | 35.00      | <b>Insulation class</b> | I       |
| <b>Dimmable</b>       | No         |                         |         |
| <b>Driver</b>         | Integrated |                         |         |
| <b>Driver type</b>    | Electronic |                         |         |

### Physical

|                    |       |
|--------------------|-------|
| <b>Color</b>       | White |
| <b>Orientation</b> | Fixed |
| <b>Weight (kg)</b> | 4.20  |

### Certification / Marking



### Note

Total consumption of the system: 56W. Light source: Up: max. 3482 lm. Down: max. 3482 lm. Luminous efficiency of luminaire: max. 138 lm/W.