

## Super Flat Suspension 30x30 Down Dimmable 1-10V

09.5001.30B1V - White

General lighting LED luminaire to be suspended from ceiling. Power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Environment</b>	Indoor
<b>Lamp category</b>	LED		
<b>Power (W)</b>	17W		
<b>Net lumen (lm)</b>	1485		
<b>Mountings</b>	Suspension		

### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	100
<b>Beam angle C90-270 (°)</b>	111



Beam Angle: 100°

h(m)	E(lx)	D(m)
1	504	2.38
2	126	4.76
3	56	7.13
4	31	9.51
5	20	11.89

Luminous flux luminaire  
1485 lm (EXTREME CUT OFF)



### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	34.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Electronic dimmable 1-10V		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	1.83

### Note

Total consumption of the system: 17W. Light source: max. 2431 lm. Luminous efficiency of luminaire: max. 143 lm/W.

### Certification / Marking

