



## Super Flat Suspension 30x30 Down No Dimmable

■ 09.5001.02B - Grey


General lighting LED luminaire to be suspended from ceiling. Power supply included.

### Main specifications

|                 |       |                |            |
|-----------------|-------|----------------|------------|
| Number of heads | 1     | Net lumen (lm) | 1485       |
| Lamp category   | LED   | Mountings      | Suspension |
| Power (W)       | 17W   | Environment    | Indoor     |
| CCT (K)         | 4000K |                |            |
| CRI             | 90    |                |            |

### Optical

|                        |            |
|------------------------|------------|
| Lighting type          | Direct     |
| LED type               | Top LED    |
| Light distribution     | Symmetric  |
| Optical type           | Wide flood |
| Beam angle (°)         | 100        |
| Beam angle C90-270 (°) | 111        |



Beam Angle: 100°

| h(m) | E(lx) | D(m)  |
|------|-------|-------|
| 1    | 504   | 2.38  |
| 2    | 126   | 4.76  |
| 3    | 56    | 7.13  |
| 4    | 31    | 9.51  |
| 5    | 20    | 11.89 |

Luminous flux luminaire  
1485 lm (EXTREME CUT OFF)

### Electrical

|                |            |                  |         |
|----------------|------------|------------------|---------|
| Frequency (Hz) | 50/60      | Emergency        | Without |
| Voltage (V)    | 34.00      | Insulation class | II      |
| Dimmable       | No         |                  |         |
| Driver         | Integrated |                  |         |
| Driver type    | Electronic |                  |         |

### Physical

|             |       |
|-------------|-------|
| Color       | Grey  |
| Orientation | Fixed |
| Weight (kg) | 1.83  |

### Note

Total consumption of the system: 17W. Light source: max. 2431 lm. Luminous efficiency of luminaire: max. 143 lm/W.

