



Super Flat Suspension 60x60 Down Dali Version

■ 09.5010.02BDA - Grey


General lighting LED luminaire to be suspended from ceiling. Power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	3627
Lamp category	LED	Mountings	Suspension
Power (W)	40W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical


Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	109
Beam angle C90-270 (°)	89



Beam Angle: 109°

	h(m)	E(lx)	D(m)
1	1038	2.81	
2	259	5.63	
3	115	8.44	
4	65	11.25	
5	42	14.06	

Luminous flux luminaire
3627 lm (EXTREME CUT OFF)



Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	34.80	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		

Physical

Color	Grey
Orientation	Fixed
Weight (kg)	3.70

Note

Total consumption of the system: 40W. Light source: max. 4821 lm. Luminous efficiency of luminaire: max. 115 lm/W.

