



## Super Flat Suspension 60x60 Down Dali Version

■ 09.5011.14BDA - Black


General lighting LED luminaire to be suspended from ceiling. Power supply included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	3775
<b>Lamp category</b>	LED	<b>Mountings</b>	Suspension
<b>Power (W)</b>	40W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	4000K		
<b>CRI</b>	90		

### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	109
<b>Beam angle C90-270 (°)</b>	89



Beam Angle: 109°

	h(m)	E(lx)	D(m)
1	1080	2.81	
2	270	5.63	
3	120	8.44	
4	68	11.25	
5	43	14.06	

Luminous flux luminaire  
3775 lm (EXTREME CUT OFF)



### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	34.80	<b>Insulation class</b>	I
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmable DALI		
	1		

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	3.70

### Note

Total consumption of the system: 40W. Light source: max. 5303 lm. Luminous efficiency of luminaire: max. 126 lm/W.

