



Super Flat Suspension 60x60 Up&Down Dali Version

■ 09.5015.14BDA - Black


General lighting LED luminaire, direct and indirect beam, to be suspended from ceiling. Power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	3408
Lamp category	LED	Mountings	Suspension
Power (W)	40W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical


Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	52
Beam angle C90-270 (°)	70



Beam Angle DIR: 52°

h(m)	E(lx)	D(m)
1	595	1.37
2	149	2.73
3	66	4.10
4	37	5.47
5	24	6.83

Luminous flux luminaire
3408 lm (EXTREME CUT OFF)



Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	34.80	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	3.70

Note

Total consumption of the system: 40W. Light source: Up: max. 2410 lm. Down: max. 2410 lm. Luminous efficiency of luminaire: max. 115 lm/W.

