



## Super Flat Suspension 60x60 Up&Down No Dimmable

■ 09.5016.02B - Grey


General lighting LED luminaire, direct and indirect beam, to be suspended from ceiling. Power supply included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	3547
<b>Lamp category</b>	LED	<b>Mountings</b>	Suspension
<b>Power (W)</b>	40W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	4000K		
<b>CRI</b>	90		

### Optical


<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	52
<b>Beam angle C90-270 (°)</b>	70



Beam Angle DIR: 52°

h(m)	E(lx)	D(m)
1	619	1.37
2	155	2.73
3	69	4.10
4	39	5.47
5	25	6.83

Luminous flux luminaire  
3547 lm (EXTREME CUT OFF)




### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	34.80	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		

### Physical

<b>Color</b>	Grey
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	3.70



### Note

Total consumption of the system: 40W. Light source: Up: max. 2651 lm. Down: max. 2651 lm. Luminous efficiency of luminaire: max. 126 lm/W.