



Super Flat Suspension 60x60 Up&Down No Dimmable

■ 09.5016.14B - Black


General lighting LED luminaire, direct and indirect beam, to be suspended from ceiling. Power supply included.

Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 3547 |
| Lamp category | LED | Mountings | Suspension |
| Power (W) | 40W | Environment | Indoor dry location |
| CCT (K) | 4000K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|------------------|
| Lighting type | Indirect, Direct |
| LED type | Top LED |
| Light distribution | Symmetric |
| Optical type | Wide flood |
| Beam angle (°) | 52 |
| Beam angle C90-270 (°) | 70 |



Beam Angle DIR: 52°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 619 | 1.37 |
| 2 | 155 | 2.73 |
| 3 | 69 | 4.10 |
| 4 | 39 | 5.47 |
| 5 | 25 | 6.83 |

Luminous flux luminaire
3547 lm (EXTREME CUT OFF)

Electrical

| | | | |
|----------------|--------------|------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 34.80 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Non Dimmable | | |

Physical

| | |
|-------------|-------|
| Color | Black |
| Orientation | Fixed |
| Weight (kg) | 3.70 |

Note

Total consumption of the system: 40W. Light source: Up: max. 2651 lm. Down: max. 2651 lm. Luminous efficiency of luminaire: max. 126 lm/W.

