



Super Flat Suspension 60x60 Up&Down No Dimmable

■ 09.5016.30B - White


General lighting LED luminaire, direct and indirect beam, to be suspended from ceiling. Power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	3547
Lamp category	LED	Mountings	Suspension
Power (W)	40W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	90		

Optical


Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	52
Beam angle C90-270 (°)	70



Beam Angle DIR: 52°

h(m)	E(lx)	D(m)
1	619	1.37
2	155	2.73
3	69	4.10
4	39	5.47
5	25	6.83

Luminous flux luminaire
3547 lm (EXTREME CUT OFF)



Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	34.80	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

Physical

Color	White
Orientation	Fixed
Weight (kg)	3.70

Note

Total consumption of the system: 40W. Light source: Up: max. 2651 lm. Down: max. 2651 lm. Luminous efficiency of luminaire: max. 126 lm/W.

