



Super Flat Suspension 90x90 Up&Down Dali Version

■ 09.5026.30BDA - White


General lighting LED luminaire, direct and indirect beam, to be suspended from ceiling. Power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	4631
Lamp category	LED	Mountings	Suspension
Power (W)	55W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	90		

Optical


Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	108
Beam angle C90-270 (°)	107



Beam Angle DIR: 108°

h(m)	E(lx)	D(m)
1	908	2.75
2	227	5.49
3	101	8.24
4	57	10.98
5	36	13.73

Luminous flux luminaire
4631 lm (EXTREME CUT OFF)



Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	35.00	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		

Physical

Color	White
Orientation	Fixed
Weight (kg)	8.30

Note

Total consumption of the system: 55W. Light source: Up: max. 3830 lm. Down: max. 3830 lm. Luminous efficiency of luminaire: max. 151 lm/W.

