



Super Line Up&Down Direct

03.9501.40 - White


LED luminaire for direct and indirect lighting with a signature minimalist and compact design, to be installed on ceilings by means of suspension. Power source included in installation kits must be ordered separately.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	5472
Power (W)	58W	Mountings	Suspension
System power (W)	60	Environment	Indoor dry location
CCT (K)	4000K		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	76
Beam angle C90-270 (°)	82
Efficiency (lm/W)	91.2




Beam Angle DIR: 76°

D(m)

E(lx)

h(m)

Luminous flux luminair
5472 lm



ENT DE LEI CE

Electrical

55.80 1050 Yes Remote Non Dimmable, Dimmable DALI Emergency Without Insulation class


Physical

Color	White
Orientation	Fixed
Weight (kg)	1.45
Length (mm)	1500
Lifespan (L70 B10)	L80B50

Note

Cable 4,25 m

Super Line Up&Down Direct




Surface Kit 60W. Dali Version 08.0521.14




Recessed Kit 60W. Non Dimmable 08.0522.14




Remote Power Supply Kit 60W. Non Dimmable 08.0524.40



Surface Kit 60W. Non Dimmable 08.0520.14




Remote Power Supply Kit 60W. Dali Version 08.0525.40



Surface Kit 60W. Non Dimmable 08.0520.02



Remote Power Supply Kit 60W. Dali Version 08.0525.14





Surface Kit 60W. Dali Version 08.0521.02



Recessed Kit 60W. Dali Version 08.0523.14







Dimmable

Remote Power Supply Kit 60W. Non Dimmable 08.0524.02

Remote Power Supply Kit 60W. Dali Version 08.0525.02









Recessed Kit 60W. Non Dimmable 08.0522.02

Recessed Kit 60W. Dali Version 08.0523.02

Recessed Kit 60W. Non Dimmable 08.0522.40







Recessed Kit 60W. Dali Version 08.0523.40

Surface Kit 60W. Non Dimmable 08.0520.40

Surface Kit 60W. Dali Version 08.0521.40