


Suspension Cone Ø 300

New

■ 03.8440.14 - Black

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.




Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1134
Power (W)	30W	Mountings	Ceiling surface
System power (W)	41	Environment	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Beam angle (°)	62
Beam angle C90-270 (°)	62
UGRL	12
Efficiency (lm/W)	27.66



Beam Angle: 62°

h(m)	E(lx)	D(m)
1	1200	1.20
2	300	2.40
3	133	3.59
4	75	4.79
5	48	5.99

Luminous flux luminaire
1134 lm

Electrical

Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III

Physical

Color	Black
Orientation	Fixed
Weight (kg)	1.75
Spot diameter (mm)	300
Lifespan (L70 B10)	L80B50

Suspension Cone Ø 300



LED power supply source for remote installation, 48V/120W. 220/240 Vac
60.9170

DALI 12-48V Dimmer
60.9678

0/1-10V & Push 12-48V Dimmer
60.9395



Casambi Controller 220-240V. Remote Installation
60.9392

LED Power Supply Source for remote installation. 48V, 100Vac (150W)-240Vac (200W)
60.9607

LED Power Supply Source for remote installation. 48V/320W, 100/240 Vac
60.8919