


## Suspension Cone Ø 300

New

### ■ 03.8442.14 - Black

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1171
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	30W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Beam angle (°)</b>	62
<b>Beam angle C90-270 (°)</b>	62



<b>Beam Angle:</b>	62°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	1238	1.20	
2	310	2.40	
3	138	3.59	
4	77	4.79	
5	50	5.99	

Luminous flux luminaire  
1171 lm

### Electrical

<b>Dimmable</b>	Yes
<b>Driver</b>	Remote excluded
<b>Emergency</b>	Without
<b>Insulation class</b>	III

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Fixed
<b>Spot diameter (mm)</b>	300

## Suspension Cone Ø 300



0/1-10V & Push 12-48V Dimmer  
60.9395



LED power supply source for remote installation, 48V/120W. 220/240 Vac  
60.9170



Casambi Controller 220-240V. Remote Installation  
60.9392



LED Power Supply Source for remote installation. 48V. 100Vac (150W)-240Vac (200W)  
60.9607



DALI 12-48V Dimmer  
60.9678



LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac  
60.8919