

Suspension Cone Ø 400

New

03.8441.14 - Black

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.

Main specifications

Number of heads	1	**CRI**	90
Lamp category	LED	**Net lumen (lm)**	1242
Power (W)	41W	**Mountings**	Ceiling surface
System power (W)	41	**Environment**	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Beam angle (°)	65
Beam angle C90-270 (°)	65
UGRL	10
Efficiency (lm/W)	30.29



Luminous flux luminaire
1242 lm

Beam Angle: 65°

h(m)	E(lx)	D(m)
1	1239	1.27
2	310	2.53
3	138	3.80
4	77	5.07
5	50	6.34

Electrical

Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III

Physical

Color	Black
Orientation	Fixed
Weight (kg)	2.85
Spot diameter (mm)	400
Lifespan (L70 B10)	L80B50

Suspension Cone Ø 400

Casambi Controller 220-240V. Remote Installation
60.9392

LED power supply source for remote installation, 48V/120W. 220/240 Vac
60.9170

LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac
60.8919

0/1-10V & Push 12-48V Dimmer
60.9395

LED Power Supply Source for remote installation. 48V. 100Vac (150W)-240Vac (200W)
60.9607

DALI 12-48V Dimmer
60.9678