


Suspension Cone Ø 400

New

03.8441.40 - White

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 2270 |
| Lamp category | LED | Mountings | Ceiling surface |
| Power (W) | 41W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Top LED |
| Light distribution | Symmetric |
| Beam angle (°) | 63 |
| Beam angle C90-270 (°) | 63 |



| Beam Angle: 63° | | |
|-----------------|-------|------|
| h(m) | E(lx) | D(m) |
| 1 | 1953 | 1.22 |
| 2 | 488 | 2.43 |
| 3 | 217 | 3.65 |
| 4 | 122 | 4.86 |
| 5 | 78 | 6.08 |


Luminous flux luminaire
2270 lm

Electrical

| | |
|-------------------------|-----------------|
| Dimmable | Yes |
| Driver | Remote excluded |
| Emergency | Without |
| Insulation class | III |

Physical

| | |
|---------------------------|-------|
| Color | White |
| Orientation | Fixed |
| Spot diameter (mm) | 400 |



Suspension Cone Ø 400



0/1-10V / DALI / PUSH Broadcast
60.9391



Casambi Controller 220-240V. Remote
Installation
60.9392



LED Power Supply Source for remote
installation. 48V/320W. 100/240 Vac
60.8919



LED Power Supply Source for remote
installation. 48V. 100Vac (150W)-240Vac
(200W)
60.9607



LED power supply source for remote
installation, 48V/120W. 220/240 Vac
60.9170