

Suspension Cone Ø 400

New

03.8443.40 - White

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.

Main specifications

Number of heads	1	**CRI**	90
Lamp category	LED	**Net lumen (lm)**	2571
Power (W)	41W	**Mountings**	Ceiling surface
System power (W)	41	**Environment**	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Beam angle (°)	63
Beam angle C90-270 (°)	63
UGRL	18
Efficiency (lm/W)	62.71



Luminous flux luminaire
2571 lm

Beam Angle: 63°

h(m)	E(lx)	D(m)
1	2212	1.22
2	553	2.43
3	246	3.65
4	138	4.86
5	88	6.08

Electrical

Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III

Physical

Color	White
Orientation	Fixed
Weight (kg)	2.85
Spot diameter (mm)	400
Lifespan (L70 B10)	L80B50

Suspension Cone Ø 400

LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac
60.8919

LED Power Supply Source for remote installation. 48V. 100Vac (150W)-240Vac (200W)
60.9607

LED power supply source for remote installation, 48V/120W. 220/240 Vac
60.9170

DALI 12-48V Dimmer
60.9678

0/1-10V & Push 12-48V Dimmer
60.9395

Casambi Controller 220-240V. Remote Installation
60.9392