

Suspension Cone ø400

■ 03.8443.14 - Black

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.


Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.

Main specifications

Number of heads	1	Net lumen (lm)	1982
Lamp category	LED	Mountings	Ceiling surface
Power (W)	41W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Beam angle (°)	65
Beam angle C90-270 (°)	65



Luminous flux luminaire
1982 lm

Beam Angle: 65°


h(m)	E(lx)	D(m)
1	1977	1.27
2	494	2.53
3	220	3.80
4	124	5.07
5	79	6.34

Electrical

Dimmable	Yes
Driver	Remote
Emergency	Without
Insulation class	III

Physical

Color	Black
Orientation	Fixed
Spot diameter (mm)	400



Suspension Cone ø400



LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac
60.8919



LED power supply source for remote installation, 48V/120W. 220/240 Vac
60.9170



Casambi Controller 220-240V. Remote Installation
60.9392



0-10V, 1-10V, DALI and PUSH interface
60.9391