

## Suspension Cone ø400

□ 03.8443.40 - White

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.

### Main specifications

<b>Number of heads</b>	1	<b>Mountings</b>	Ceiling surface
<b>Lamp category</b>	LED	<b>Environment</b>	Indoor
<b>Power (W)</b>	41W		
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric

### Electrical

<b>Dimmable</b>	Yes
<b>Driver</b>	Remote
<b>Emergency</b>	Without
<b>Insulation class</b>	III


### Physical

<b>Color</b>	White
<b>Orientation</b>	Fixed
<b>Spot diameter (mm)</b>	400

### Note

Preliminary photometry

### Certification / Marking



## Suspension Cone ø400



LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac  
60.8919



LED Power Supply Source for remote installation. 48V/185W. 100/240 Vac  
60.9024



LED power supply source for remote installation, 48V/120W. 220/240 Vac  
60.9170



Casambi Broadcast. Remote Installation  
60.9392



0-10V, 1-10V, DALI and PUSH interface  
60.9391