



## Suspension Glass Downlight 110 Black Rod 100 mm Dali Version

■ 03.8132.00.DA - Transparent Glass


Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.

### Main specifications

<b>Number of heads</b>	1	<b>CRI</b>	90
<b>Lamp category</b>	LED	<b>Net lumen (lm)</b>	746
<b>Power (W)</b>	13.5W	<b>Mountings</b>	Track
<b>System power (W)</b>	14	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		

### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	82
<b>Beam angle C90-270 (°)</b>	82
<b>Efficiency (lm/W)</b>	53.29



Beam Angle: 82°

	h(m)	E(lx)	D(m)
1	474	1.74	
2	119	3.48	
3	53	5.22	
4	30	6.96	
5	19	8.71	

Luminous flux luminaire  
746 lm



### Electrical

<b>Voltage (V)</b>	48	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmable DALI		
	1		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Transparent
	Glass
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.98
<b>Length (mm)</b>	205
<b>Lifespan (L70 B10)</b>	L80B50

### Note

Only compatible with DALI profile version.

