



## Suspension Glass Downlight 110 Black Rod 100 mm Dali Version

■ 03.8132.RC.DA - Red Glass


Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	309
Power (W)	13.5W	Mountings	Track
System power (W)	14	Environment	Indoor dry location
CCT (K)	3000K		


### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	42
Beam angle C90-270 (°)	42
UGRL	15
Efficiency (lm/W)	22.07



Beam Angle:	42°		
	h(m)	E(lx)	D(m)
1	459	0.76	
2	115	1.52	
3	51	2.28	
4	29	3.04	
5	18	3.80	

Luminous flux luminaire  
309 lm



### Electrical

Voltage (V)	48	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable DALI		
	1		
Emergency	Without		

### Physical

Color	Red Glass
Orientation	Fixed
Weight (kg)	0.98
Length (mm)	205
Lifespan (L70 B10)	L80B50

### Note

Only compatible with DALI profile version.

