



Suspension Glass Downlight 110 Black Rod 100 mm Dimmable 1-10V

03.8132.FU.1V - Smoked Glass


Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	510
Power (W)	13.5W	Mountings	Track
System power (W)	14	Environment	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	47
Beam angle C90-270 (°)	47
Efficiency (lm/W)	36.43



Beam Angle:	47°		
	h(m)	E(lx)	D(m)
1	474	0.86	
2	119	1.72	
3	53	2.58	
4	30	3.45	
5	19	4.31	

Luminous flux luminaire
510 lm



Electrical

Voltage (V)	48	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable 1-10V		
Emergency	Without		

Physical

Color	Smoked Glass
Orientation	Fixed
Weight (kg)	0.98
Length (mm)	205
Lifespan (L70 B10)	L80B50

Note

Only compatible with 1-10V profile version.

